

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 08-Apr-2010 Revision Date 30-Nov-2024 Revision Number 6

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: Potassium hydroxide, 0.1N Standardized Solution in methanol

Cat No. : 42736

Synonyms Potassium hydroxide solution 0.1M (0.1N); Methyl hydroxide; Carbinol; Methanol;

Monohydroxymethane; Pyroxylic spirit; Wood alcohol; Wood naphtha; Wood spirit; Methyl

hydrate

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

**Process categories** PROC15 - Use as a laboratory reagent

**Environmental release category** ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

## 1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency

information services

Ireland: National Poisons Information Centre (NPIC) -

**01 809 2166** (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

ALFAA42736

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

Revision Date 30-Nov-2024

Flammable liquids Category 2 (H225)

#### **Health hazards**

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Specific target organ toxicity - (single exposure)

Category 3 (H301)

Category 3 (H311)

Category 3 (H331)

Category 1 (H370)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

**Danger** 

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

	Component	CAS No	EC No	Weight %	GHS Classification - According to
- 1					GB-CLP Regulations UK SI 2019/720 and

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

				UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	> 99	Flam. Liq. 2 (H225)
				Acute Tox. 3 (H301)
				Acute Tox. 3 (H311)
				Acute Tox. 3 (H331)
				STOT SE 1 (H370)
Potassium hydroxide	1310-58-3	215-181-3	< 1	Met. Corr. 1 (H290)
				Acute Tox. 4 (H302)
				Skin Corr. 1A (H314)
				Eye Dam. 1 (H318)
				· , ,

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-
Potassium hydroxide	Skin Corr. 1A (H314) :: C>=5% Skin Corr. 1B (H314) :: 2%<=C<5% Skin Irrit. 2 (H315) :: 0.5%<=C<2% Eye Irrit. 2 (H319) :: 0.5%<=C<2%	-	-

Components	Reach Registration Number	
Methanol	01-2119433307-44	
Potassium hydroxide	01-2119487136-33	

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

**Self-Protection of the First Aider** Use personal protective equipment as required.

## 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

## 4.3. Indication of any immediate medical attention and special treatment needed

ALFAA42736

## Potassium hydroxide, 0.1N Standardized Solution in methanol

**Notes to Physician** 

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

No information available.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Thermal decomposition can lead to release of irritating gases and vapors. Vapors may form explosive mixtures with air. Flammable/toxic gases may accumulate in confined areas (basements, tanks, hopper/tank cars etc.). Vapors may travel to source of ignition and flash back. Vapors from liquefied gas are initially heavier than air and spread along ground. Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Formaldehyde, Thermal decomposition can lead to release of irritating gases and vapors.

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

AL DA A 40720

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

Class 3

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m³ TWA	TWA: 260 mg/m <sup>3</sup> 8 hr	TWA: 260 mg/m <sup>3</sup> 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m <sup>3</sup> STEL		STEL: 780 mg/m <sup>3</sup> 15 min
			Skin
Potassium hydroxide	WEL - 2 mg/m <sup>3</sup> STEL		STEL: 2 mg/m <sup>3</sup> 15 min

#### **Biological limit values**

List source(s):

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
67-56-1 ( > 99 )		bw/day		bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 ( > 99 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>
Potassium hydroxide 1310-58-3 ( < 1 )			DNEL = 1mg/m <sup>3</sup>	

## **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)

## Potassium hydroxide, 0.1N Standardized Solution in methanol

		sediment		sewage treatment	
Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
67-56-1 ( > 99 )		sediment dw			soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol 67-56-1 ( > 99 )	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

#### 8.2. Exposure controls

## **Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** 

Goggles Tight sealing safety goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	> 480 minutes	0.35 mm	Level 6	As tested under EN374-3 Determination of
Butyl rubber	> 480 minutes	0.70 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 60 minutes	0.45 mm		
Nitrile rubber	< 30 minutes	0.38 mm		

Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

ALFAA42736

Potassium hydroxide, 0.1N Standardized Solution in methanol

Physical State Liquid

Appearance Clear, Colorless
Odor Alcohol-like
Odor Threshold No data available
Melting Point/Range No data available
Softening Point No data available
Boiling Point/Range 64.7 °C / 148.5 °F

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 12 °C / 53.6 °F Method - No information available

Autoignition Temperature 455 °C / 851 °F Decomposition Temperature 455 °C / 851 °F No data available

oH > 13

Viscosity No data available

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74Potassium hydroxide0.83

Vapor Pressure No data available

Density / Specific Gravity 0.8

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Acids. Acid anhydrides. Acid chlorides. halocarbons. Isocyanates. Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Thermal decomposition can

lead to release of irritating gases and vapors.

Revision Date 30-Nov-2024

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

Oral Category 3 **Dermal** Category 3 Inhalation Category 3

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h
Potassium hydroxide	LD50 = 333-384 mg/kg (Rat)	-	<del>-</del>

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Based on available data, the classification criteria are not met Respiratory Based on available data, the classification criteria are not met Skin

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 ( > 99 )	Guinea Pig Maximisation Test		_
	(GPMT)		

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(a) reproductive toxicity: Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 ( > 99 )		2 Generation	1.3 mg/l (air)

(h) STOT-single exposure; Category 1

Optic nerve, Central nervous system (CNS). Results / Target organs

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Revision Date 30-Nov-2024

## **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

**Ecotoxicity effects** 

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 >	EC50 > 10000 mg/L 24h	
•	10000 mg/L 96h	-	
Potassium hydroxide	LC50 = 50-165 mg/L (96h)		

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	

#### 12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.

Component	Degradability	
Methyl alcohol	DT50 ~ 17.2d	
67-56-1 ( > 99 )	>94% after 20d	

#### 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Potassium hydroxide	0.83	No data available

The product contains volatile organic compounds (VOC) which will evaporate easily from all 12.4. Mobility in soil

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste treatment methods

Waste from Residues/Unused Waste is classified as hazardous. Dispose of in accordance with the European Directives

Potassium hydroxide, 0.1N Standardized Solution in methanol

Revision Date 30-Nov-2024

**Products** on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Solutions with high pH-value must be neutralized before discharge.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

**14.1. UN** number UN1230 **14.2. UN** proper shipping name METHANOL

14.3. Transport hazard class(es) 3 Subsidiary Hazard Class 6.1 14.4. Packing group II

#### ADR

**14.1. UN number** UN1230 **14.2. UN proper shipping name** WETHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

#### IATA

14.1. UN number UN1230
14.2. UN proper shipping name METHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

14.5. Environmental hazards No hazards identified

**14.6. Special precautions for user** No special precautions required.

<u>14.7. Maritime transport in bulk</u> according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

ALFAA42736

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Potassium hydroxide	1310-58-3	215-181-3	-	-	X	X	KE-29139	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	X	Ī	X	Χ	X
Potassium hydroxide	1310-58-3	X	ACTIVE	X	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Potassium hydroxide	1310-58-3	-	Use restricted. See entry 75. (see link for restriction details)	-

## **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report
		Notification	Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Potassium hydroxide	1310-58-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** Water endangering class = 2 (self classification)

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)
Potassium hydroxide	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol 67-56-1 ( > 99 )	Prohibited and Restricted Substances	Group I	
Potassium hydroxide 1310-58-3 ( < 1 )	Prohibited and Restricted Substances		

#### 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

## Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

**ALFAA42736** 

#### Potassium hydroxide, 0.1N Standardized Solution in methanol

Revision Date 30-Nov-2024

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Health, Safety and Environmental Department **Prepared By** 

**Creation Date** 08-Apr-2010 **Revision Date** 30-Nov-2024 **Revision Summary** Not applicable.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**

**ALFAA42736**